



Product Type: Plug-in terminal-Socket

Product Name:MC-  
PHP7.62H03C-F-0001

Product Description: Pitch: 7.62mm Rated  
Voltage : 630V Rated Current: 20A  
colour : customizable

Parameters

|                               |                                  |
|-------------------------------|----------------------------------|
| ⌘ SUPU ID                     | MC-PHP7.62H03C-F-0001            |
| ⌘ Pitch                       | 7.62                             |
| ⌘ Number of connections       | 3                                |
| ⌘ Connection method           | 螺钉接线                             |
| ⌘ Protection Level            | IP20                             |
| ⌘ Operating temperature range | -40~+105℃                        |
| ⌘ Insulation material         | PA66                             |
| ⌘ Insulation material group   | I                                |
| ⌘ Contact material            | Copper alloy                     |
| ⌘ Contact plating             | Sn,Plated                        |
| ⌘ Color                       | Green/Black/Blue/Grey/Orange/Red |

Technical data

|                     |      |
|---------------------|------|
| ⌘ IEC Rated Current | 630V |
| ⌘ IEC Rated Voltage | 20A  |

|                                                 |                         |
|-------------------------------------------------|-------------------------|
| ☞ Overvoltage category                          | III III II              |
| ☞ Degree of pollution                           | 3 2 2                   |
| ☞ Rated impulse voltage                         | 6.0KV 6.0KV 6.0KV       |
| ☞ UL Rated Current                              | 35A - 10A               |
| ☞ UL Rated Voltage                              | 300V - 300V             |
| ☞ Conductor cross section rigid                 | 0.2-4.0mm <sup>2</sup>  |
| ☞ Conductor cross section flexible              | 0.2-4.0mm <sup>2</sup>  |
| ☞ Conductor cross section flexible,with furrule | 0.25-2.5mm <sup>2</sup> |
| ☞ Locking screw Specification                   | M3                      |
| ☞ Locking screw torque                          | 0.5N.m                  |
| ☞ Fixed Screw Specification                     | M3                      |
| ☞ Stripping length                              | 8-9mm                   |
| ☞ Use group                                     | B/C/D                   |

## Commercial data

|            |                       |
|------------|-----------------------|
| ☞ Order No | MC-PHP7.62H03C-F-0001 |
|------------|-----------------------|

## Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,  
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat

---

Date:2026-02-26 23:44

The right to modify data belongs to SUPU.