


Product Type: Push-in spring terminal

## Product Name:TPH35-2-GY

Product Description: Connection method:Push in connection,Number of connections:2,Number of levels : 1

### Product Size



### Parameters

|                         |            |
|-------------------------|------------|
| ⌘ SUPU ID               | TPH35-2-GY |
| ⌘ Width                 | 16mm       |
| ⌘ Number of levels      | 1          |
| ⌘ Number of connections | 2          |

|  |              |
|--|--------------|
| ☞ Connection method                        | 直插弹簧接线       |
| ☞ Protection Level                         | IP20         |
| ☞ Insulation material                      | PA66         |
| ☞ Insulation material group                | I            |
| ☞ Contact material                         | Copper alloy |
| ☞ Contact plating                          | Sn,Plated    |
| ☞ Ambient temperature (operation)          | -40°C~105°C  |
| ☞ Ambient temperature (assembly)           | -5°C~70°C    |
| ☞ Ambient temperature (storage)            | -25°C~60°C   |
| ☞ Permissible humidity (storage/transport) | 30%~70%      |

## Technical data

|   |                       |
|---|-----------------------|
| ☞ IEC Rated Current                             | 125A                  |
| ☞ IEC Rated Voltage                             | 1000V                 |
| ☞ Overvoltage category                          | III                   |
| ☞ Degree of pollution                           | 3                     |
| ☞ Rated impulse voltage                         | 8KV                   |
| ☞ UL Rated Current                              | 115A/115A/-           |
| ☞ UL Rated Voltage                              | 1000V/1000V/-         |
| ☞ Conductor cross section rigid                 | 2.5-35mm <sup>2</sup> |
| ☞ Conductor cross section flexible              | 2.5-35mm <sup>2</sup> |
| ☞ Conductor cross section flexible,with ferrule | 2.5-35mm <sup>2</sup> |
| ☞ Stripping length                              | 25mm                  |
| ☞ Use group                                     | B/C/D                 |

Commercial data

☞ Order No

TPH35-2-GY

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,  
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat