





Product Type: Barrier terminal

Product Name:TB-K-16.0V12C-001

Product Description: pitch : 16.0mm, rated voltage UL600V, rated current UL75A, color: black, Rated cross section 22-4AWG

Product Size



Parameters

⌘ SUPU ID	TB-K-16.0V12C-001
⌘ Pitch	16.0
⌘ Number of levels	single layer
⌘ Number of connections	12
⌘ Connection method	Screw connection
⌘ Protection Level	IP20
⌘ Operating temperature range	-30°C ~+120°C
⌘ Insulation material	PBT+GF

☞ Insulation material group	III
☞ Contact material	Copper alloy
☞ Contact plating	Sn plated

Technical data

☞ IEC Rated Current	75/75/75
☞ IEC Rated Voltage	1000/1000/1000
☞ Overvoltage category	III/III/II
☞ Degree of pollution	3/2/2
☞ Rated impulse voltage	/
☞ Conductor cross section rigid	16-25
☞ Stripping length	12-13
☞ Tightening torque	44.27
☞ Connection capacity AWG	22-4
☞ UL Rated Current	75/75/5
☞ UL Rated Current	600/600/600

Commercial data

☞ Order No	TB-K-16.0V12C-001
------------	-------------------

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Ningbo SUPU Electronics Co., Ltd.

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat

Date:2025-11-27 17:09

The right to modify data belongs to SUPU.