


Product Name:MC-PA7.5H13-F-0002



Technical drawing of the PCB layout for the 4-channel relay module. The drawing includes three views: a side profile, a top view, and a bottom view.

Side Profile View:

- Overall height: 3.50 ± 0.30
- Base width: 12.00
- Mounting tab width: 2.00
- Relay body height: 7.80
- Terminal pin height: 8.45

Top View:

- Channel pitch: 7.50
- Mounting hole diameter: $\square 1.00$
- Relay body width: 9.00
- Terminal pin width: 6.10
- Overall width: $\text{Dim. } a = 7.50 \times (P-1)$
- Overall length: $\text{Dim. } b = 7.50 \times (P-1) + 18.00$

Bottom View (PCB LAYOUT):

- Mounting hole diameter: $\phi 1.40$
- Terminal pin diameter: $\phi 2.40$
- Mounting hole pitch: 7.50
- Mounting hole offset: 4.50
- Terminal pin offset: 2.00
- Overall width: 12.00
- Overall length: 6.10

⌘ SUPU ID	MC-PA7.5H13-F-0002
⌘ Pitch	7.5
⌘ Number of levels	Single layer
⌘ Number of connections	13

☞ Connection method	-
☞ Protection Level	IP20
☞ Operating temperature range	-40~+105°C
☞ Insulation material	PA66
☞ Insulation material group	I
☞ Contact material	Copper alloy
☞ Contact plating	Sn,Plated
☞ Color	Green/Black/Blue/Grey/Orange/Red

Technical data

☞ IEC Rated Current	630V
☞ IEC Rated Voltage	18A
☞ Overvoltage category	III III II
☞ Degree of pollution	3 2 2
☞ Rated impulse voltage	6.0KV 6.0KV 6.0KV
☞ UL Rated Current	15A - 10A
☞ UL Rated Voltage	300V - 300V
☞ Conductor cross section rigid	-
☞ Conductor cross section flexible	-
☞ Conductor cross section flexible,with furrule	-
☞ Locking screw Specification	-
☞ Locking screw torque	-
☞ Fixed Screw Specification	-
☞ 固定螺钉扭矩	-

☞ Stripping length	-
☞ Use group	B/C/D
☞ Rated cross section	-

Commercial data	
☞ Order No	MC-PA7.5H13-F-0002

Ningbo SUPU Electronics Co., Ltd.
 Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,
 Cixi City, Zhejiang Province, China
 Zip code: 315303
 Switchboard: +86 574-63288158
 Fax: +86 574-63288170
 E-mail:supucontact@supu.cn
 Service Hotline: 400-626-6336



Wechat