





Product Type: Screw terminal

Product Name: TU2.5-4-GY

Product Description: Connection method: Screw connection, IEC Rated current: 24A, IEC Rated Voltage: 1000V, Number of connections: 4, Number of levels : 1, Rated cross section: 26-12AWG

Product Size



Parameters

 SUPU ID	TU2.5-4-GY
 Width	5.2mm
 Number of levels	1
 Number of connections	4

☞ Connection method	Screw connection
☞ Protection Level	IP20
☞ Insulation material	PA66
☞ Insulation material group	I
☞ Contact material	Copper alloy
☞ Contact plating	Sn,Plated
☞ Ambient temperature (operation)	-40°C~105°C
☞ Ambient temperature (assembly)	-5°C~70°C
☞ Ambient temperature (storage)	-25°C~60°C
☞ Permissible humidity (storage/transport)	30%~70%
☞ Product type	Terminal block of side-entry

Technical data

☞ IEC Rated Current	24A
☞ IEC Rated Voltage	1000V
☞ Overvoltage category	III
☞ Degree of pollution	3
☞ Rated impulse voltage	8kV
☞ UL Rated Current	20/20/5A
☞ UL Rated Voltage	300/300/600V
☞ Conductor cross section rigid	0.2-4mm ²
☞ Conductor cross section flexible	0.2-2.5mm ²
☞ Conductor cross section flexible,with furrule	0.2-2.5mm ²
☞ Locking screw Specification	M2.5

⌘ Locking screw torque	0.4N.m
⌘ Fixed Screw Specification	/
⌘ 固定螺钉扭矩	/
⌘ Stripping length	9-11mm
⌘ Use group	B/C/D
⌘ Rated cross section	26-12AWG
⌘ UL Rated Current	20/20/5A
⌘ UL Rated Current	300/300/600V

Commercial data

⌘ Order No	TU2.5-4-GY
------------	------------

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,

Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Date:2026-03-02 02:08

The right to modify data belongs to SUPU.