



Product Type: Plug-in terminal-Socket

Product Name:MC-

PQ7.62HXXP-F-0001

Product Description: Pitch:7.62mm Rated

Voltage : 1000V Rated Current:41A Connection

method : Push-in spring connection

colour : customizable

Parameters

| | |
|-------------------------------|----------------------------------|
| ☞ SUPU ID | MC-PQ7.62HXXP-F-0001 |
| ☞ Pitch | 7.62 |
| ☞ Number of connections | XX |
| ☞ Connection method | Push in spring connection |
| ☞ Protection Level | IP20 |
| ☞ Operating temperature range | -40~+105°C |
| ☞ Insulation material | PA66 |
| ☞ Insulation material group | I |
| ☞ Contact material | Copper alloy |
| ☞ Contact plating | Sn,Plated |
| ☞ Color | Green/Black/Blue/Grey/Orange/Red |

Technical data

| | |
|---------------------|-----|
| ☞ IEC Rated Current | 41A |
|---------------------|-----|

| | |
|---|-------------------------|
| ☞ IEC Rated Voltage | 1000V |
| ☞ Overvoltage category | III/III/II |
| ☞ Degree of pollution | 3 2 2 |
| ☞ Rated impulse voltage | 8.0KV 8.0KV 8.0KV |
| ☞ UL Rated Current | 35A - 35A |
| ☞ UL Rated Voltage | 600V - 600V |
| ☞ Conductor cross section rigid | 0.2~10.0mm ² |
| ☞ Conductor cross section flexible | 0.2~10.0mm ² |
| ☞ Conductor cross section flexible,with ferrule | 0.2~6.0mm ² |
| ☞ Locking screw Specification | - |
| ☞ Locking screw torque | - |
| ☞ Fixed Screw Specification | - |
| ☞ Stripping length | 13~15mm |
| ☞ Use group | B/C/D |

Commercial data

| | |
|------------|----------------------|
| ☞ Order No | MC-PQ7.62HXXP-F-0001 |
|------------|----------------------|

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,

Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat

Date:2026-03-10 03:58

The right to modify data belongs to SUPU.