



DPAN3.5H32-D-BK-2600

Product Description: Pitch:3.5mm Rated

Voltage : 160V Rated Current:8A

colour : customizable

The drawing consists of three views of the n2ns 915W40-01 module:

- Top View:** Shows a rectangular module with a width of 13.30 and a height of 15.20. The mounting tab width is 2.60. The distance between the mounting holes is 3.50, and the distance from the edge to the first hole is 9.20.
- Side View:** Shows the module's profile with a height of 8.30. The mounting holes are spaced at $3.5 \times (P/2 - 1)$ and the total width of the hole array is $3.5 \times (P/2 - 1) + 4.9$. The distance from the edge to the first hole is 2.45.
- PCB LAYOUT:** Shows the footprint of the module on the PCB. The mounting holes are spaced at 3.50, and the total width of the hole array is $3.5 \times (P/2 - 1)$. The distance from the edge to the first hole is 2.45. The distance between the mounting holes is 9.20, and the distance from the edge to the first hole is 3.50. A reference dimension of $\phi 1.4$ is indicated for the mounting holes.

MC-DPAN3.5H32-D-BK-2600



3.5

 Number of levels

double-layer

 Number of connections

32

☞ Connection method	-
☞ Protection Level	IP20
☞ Operating temperature range	-40~+105°C
☞ Insulation material	PA66
☞ Insulation material group	I
☞ Contact material	Copper alloy
☞ Contact plating	Sn,Plated
☞ Color	Green/Black/Blue/Grey/Orange/Red

Technical data

☞ IEC Rated Current	160V
☞ IEC Rated Voltage	8A
☞ Overvoltage category	III III II
☞ Degree of pollution	3 2 2
☞ Rated impulse voltage	2.5KV 2.5KV 2.5KV
☞ UL Rated Current	8A - 8A
☞ UL Rated Voltage	150V - 150V
☞ Conductor cross section rigid	-
☞ Conductor cross section flexible	-
☞ Conductor cross section flexible,with furrule	-
☞ Locking screw Specification	-
☞ Locking screw torque	-
☞ Fixed Screw Specification	-
☞ 固定螺钉扭矩	-

☞ Stripping length	-
☞ Use group	B/C/D
☞ Rated cross section	-

Commercial data

☞ Order No	MC-DPAN3.5H32-D-BK-2600
------------	-------------------------

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,

Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat