



Product Description: Pitch: 7.62mm Rated
Voltage : 630V Rated Current: 41A
colour : customizable

Figure 1: PCB layout of the 100W LED module. The diagram shows three views: a side view, a top view, and a bottom view. The side view shows a height of 14.30, a mounting hole diameter of 1.00x0.80, and a base width of 5.00. The top view shows a total width of $7.62 \times (P-1) + 8.60$, with individual hole spacing of 7.62 and a total length of 4.30 (5.10). The bottom view shows a total width of $7.62 \times (P-1)$, with individual hole spacing of 7.62 and a total length of 4.30 (5.10). A reference hole of diameter 1.40 is also indicated.

SUPU ID	MC-PHH7.62H07-I-0001
Pitch	7.62
Number of levels	Single layer
Number of connections	7

☞ Connection method	-
☞ Protection Level	IP20
☞ Operating temperature range	-40~+105°C
☞ Insulation material	PA66
☞ Insulation material group	I
☞ Contact material	Copper alloy
☞ Contact plating	Sn,Plated
☞ Color	Green/Black/Blue/Grey/Orange/Red

Technical data

☞ IEC Rated Current	630V
☞ IEC Rated Voltage	41A
☞ Overvoltage category	III III II
☞ Degree of pollution	3 2 2
☞ Rated impulse voltage	6.0KV 6.0KV 6.0KV
☞ UL Rated Current	41A 41A 10A
☞ UL Rated Voltage	300V 150V 300V
☞ Use group	B/C/D

Commercial data

☞ Order No	MC-PHH7.62H07-I-0001
------------	----------------------

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat

Date:2026-03-04 10:01

The right to modify data belongs to SUPU.